

Ultra-thin structure design, transparent light guide effect, coupled with perfect process details, the product appearance looks rich in texture. This product is DIY assembled, no needprofessionals, portable on one side of the desktop, easy to install, flexible to use. Typicallight efficiency is 100LM/W, flicker free. Controlled by touching panel, it can realize 50% DIRECT / 50% INDIRECT lighting synchronous dimming. Designed with square corner, and its main materials are aluminum profiles, steel plates and PMMA, suitable for Small office areas or Home office and other office application scenarios.

Features

Simple, slim, delicate appearance, patent design with rich texture

Touch panel dimming

SDCM < 3

L80, B10 @50000H


5 years warranty




Application Areas

For personal offices, public offices and other office space.







Item No.	BLAF-1905527-BN
Input Power	↑27.5W/27.5W↓
Input Voltage	AC200~240V
Power Factor	≥0.9
Luminous Flux	↑2200lm/3300lm↓
UGR	< 22
Color Rendering Index	>80
Life Time	L80(B10)50,000H
Beam Angle	↑160°/150°↓
CCT	3000/4000/6000K
Colour consistency SDCM	< 3
Dimming	Touch panel dimming
Light Control	NO
Housing Color	Silver/White
Fixture Materia	6063AL
Protection Level	IP20
Storage Temperature	-40°C∼+80°C
Working Temperature	-20°C∼+45°C
Net Weight	10kg
Package size	2040*180*260mm 720*390*130mm
20GP	396pcs
40GP	860pcs

Shenzhen Nexol Lighting Technology Co.,Ltd.

E-mail: <u>info@nexol-lighting.com</u>

www.nexol-lighting.com

Factory: Floor 6-9, Building 3, Tonghu Intelligent Industrial Park, Zhongkai High-Tech District, HuiZhou 516035

Office: Room 306&309, Floor 3, Building E, Longhua Digital Industrial Park, Guanlan Road 54-6, Longhua district, Shenzhen, China 518110

