

Simply and reasonable structure design with excellent craftwork. Appearance with rich texture. Reliable heat dissipation system. 5years warranty. Typical value up to 100lm/W with flicker freely. 1-10V and Dali synchronous dimming, support CASAMBI wireless system. Profile aluminum, PMMA as main materials, Surface mounted installation. Easy & Fast.

## **Features**

Simple but delicate design

Easy for maintenance

Light efficiency could be 100LM/W

Simple, easy and quick installation

Support for smart control functions

- DALI dimming
- 1-10V dimming
- tunable white

5 years warranty




For open-plan office, reception, training room, cafeteria, etc.









Item No.	BLIC-1204040-NN	BLIC-1204040-VN	BLIC-1204040-DN	
Input Power	40W			
Input Voltage	AC200~240V			
Power Factor	≥0.9			
Luminous Flux	3600lm			
UGR	<21			
Color Rendering Index	>80			
Life Time	L80(B10)50,000H			
Beam Angle	80°			
CCT	3000/4000/6000K			
Colour consistency SDCM	< 3			
Dimming	NO	1-10V dimming	DALI dimming	
	NO			
Sensor		NO		
Sensor Housing Color		NO Silver/White		
Housing Color		Silver/White		
Housing Color Fixture Materia		Silver/White 6063AL		
Housing Color Fixture Materia Protection Level		Silver/White 6063AL IP20		
Housing Color Fixture Materia Protection Level Storage Temperature		Silver/White 6063AL IP20 -40°C~+80°C		
Housing Color Fixture Materia Protection Level Storage Temperature Working Temperature		Silver/White 6063AL IP20 -40°C~+80°C -20°C~+45°C		
Housing Color Fixture Materia Protection Level Storage Temperature Working Temperature Net Weight		Silver/White 6063AL IP20 -40°C~+80°C -20°C~+45°C 2.7kg		



## **Technical data**

Item No.	BLIC-1505050-NN	BLIC-1505050-VN	BLIC-1505050-DN	
Input Power	50W			
Input Voltage	AC200~240V			
Power Factor	≥0.9			
Luminous Flux	4500lm			
UGR	<21			
Color Rendering Index	>80			
Life Time	L80(B10)50,000H			
Beam Angle	80°			
CCT	3000/4000/6000K			
Colour consistency SDCM	< 3			
Dimming	NO	1-10V dimming	DALI dimming	
Sensor	NO			
Housing Color	Silver/White			
Fixture Materia	6063AL			
Protection Level	IP20			
Storage Temperature	-40°C∼+80°C			
Working Temperature	-20°C~+45°C			
Net Weight	3.6kg			
Package size	1660*315*335mm			
20GP	1096PCS			
40GP	2416PCS			



E-mail: info@nexol-lighting.com

www.nexol-lighting.com

Factory: 3&4th F, Building A3, Xin-Gui-Yuan Industrial Park, DaFu Road, GuanLan Town, ShenZhen, China 518110 Office: 5th F, Building A1, Zhang-Ge Techno Park, GuanLan Town, ShenZhen, China 518110

